PURCHASE ORDER

Municipal Government of Santa Fe, Romblon LGU

Address : Santa Ana, Manila			P.O. No. : <u>2024-03-0019</u> Date : <u>March 8, 2024</u> Mode of Procurement : <u>Public Bidding</u> PR No./s : <u>2024-01-0006</u> / January 11, 2024			
Gentlemen:			I K 110./3 . 2024	-01-0000 7 ounuar	, 11, 2021	
Please furn		fice the following articles subject to the terms and conditions				
Place of Delivery : <u>Tai</u>			Delivery Term : <u>Deliver at the Jobsite</u> Payment Term : <u>Check</u>			
		king Days after the Receipt of NTP		Unit Cost	Amount	
Stock No.	Unit	Description	Quantity	Unit Cost		
2024-01484411	set	CERVICAL INSPECTION SET OR VAGINAL SPECULUM SET	1	18,000.00	18,000.00	
		All instruments are made of Stainless Steel				
		High Quality				
		Autoclavable				
		Dimension: 1x1x1				
2024-0149-4411	set	DRESSING SET OR MINOR SURGERY SET	1	5,200.00	5,200.0	
		 stainless steel, resistant to rust and corrosion 				
		innert to chemical reaction				
		 ergonomically designed 				
		high tensile				
	Assessed Misself	sterilizable				
		reusable				
2024-0150-4411	unit	EXAMINING LIGHT	1	22,500.00	22,500.0	
		 Heavy base with low centre of gravity 				
		 Single light head with LED lights in cluster 				
	207	Articulating arm between light and base stand				
		 Base with 5 anti-static swivel castors in a star formation 				
		At least two castors have been equipped with brakes				
		Minimum 14cm fixed focus field of view				
		Minimum illuminatio of 60,000 lux at 0.5m				
		Minimum colour temperature between 4,000 K				
		Minimum colour rendering index (CRI) of 9.	5			
		Minimum LED life more than 40,000 hours				
		 Floor to light height adjustable to include at least range of 1.1 m to 1.75 m. 				
		On/Off switch				
		 Power requirements 220-240 volts- 50/60 Hz. 				
		 Supplied with Instructions for assembly, use and maintenance in English 			1100	
2024-0151-4411	unit	EXAMINING TABLE WITH FOOT STOOL	1	16,875.00	16,875.	
		Stainless Steel top 3 section adjustable				
		with stainless steel heel detachable stirrup	s			
		with mattress and leatherette cover at leas 4" inches thick	t			
		with stainless steel drain pan				
		table with drawers				
-		sub-total			62,575.	

at least 1 year	C4 1 37	TT **	-PO Number 2024-03-0019-	One-4'+-	Unit Coat	Amorina
bible top dimension (shanderd size) versual functions (minimum) at least to with Vince dimension (minimum) at least to with Vince with horix state of size with Vince with horix vith ultre-strong uni-frame constructed bible and top finance provides a rigid plate. 2024-0153-4411 unit STRUMENT TABLE Morebible height adjustable instrument table, mays by an horizontal vitable. The strong of the size of the siz	Stock No.	Unit		Quantity	Unit Cost	Amount
• overall dimension (minimum) at least W56m_11-50.H 30cm • standard size with IV pole with hook • with ultra-storp unif-frame constructed bases and top fame provides a rigid patient of a least and top fame provides a rigid patient of a least start pater provides a rigid patient of a least start year and start year 2024-0153-4411	4				 	
W. SECR. L. 180, H. SECRE Standard Size with If Vipe with hock						
## with uthra-strong un-Frame constructed beserved tog frame provides and gifty patient		- 2.2				
bese and top frame provides a rigid patient 3,600.00 3,750.00 3			standard size with IV pole with hook			
SULCOMETER, with needle and 100 strips, with expiration of at a 3,600.00 3,600.00 3,600.00 3,750.00			with ultra-strong uni-frame constructed			
at least 1-year 1 3,00,00 3,750.00 3,75						
Movable height adjustable instrument table, may be heavy carriage mounted on 4 swivel casters of which two with brake and 4 with andistation wheel Pessioning under love clearner table (e.g. operating table) Post of the base operating table) Post of the base operating table) Post of the base operating table of the base operating table of the base operating table of the base of the base operating table of the base of th	2024-0152-4411	unit		1	3,600.00	3,600.00
table, mayo type • heavy carriage mounted on 4 swivel castors of which two with brake and 4 with anti-static wheel • support column side-on base, facilities positioning under low clearance table (e.g. operating table) • both castors with brake mounted at the short side of the base • solid manual level allows setting telescopic upper part at required height of the base and the short side of the	2024-0153-4411	unit	INSTRUMENT TABLE	1	3,750.00	3,750.00
heavy carriage mounted on 4 swivel casters of which two with brake and 4 with antistation wheel support column side-on base, facilities positioning under lov clearance table (e.g. operating table) both castors with brake mounted at the short side of the base solid manual level allows setting telescopic upone part at required height sa brake prevents exceeding the maximum height setting upper section fit with smooth finished removable instrument bay Material: high resistance to corrosion (tropical environment) strame and tray: Austeratic stainless steel, gardes 304 caster finance total-lock type (wheel and rotational lock) caster finance strotal-lock type (wheel and rotational lock) caster strame single wheel, motion trype, non-hooded (for easy maintenance), anti-static (for 4) wheel bearing: seeled bearing in the swivel and the wheel swivel is ball bearing Oimansion: Overall (81-90) x (50-55) x (90-100) cm (i/Wh1) frame 2,7-3,3 cm (outside, across), 1.5 mm thickness wivelocess shelves: 1,35-1,5mm swivel castor wheel: 2x10 cm (w*diameter) ecrypring capacity: 100kg hooks extrame the same transport of the same tra						
positioning under low clearance table (e.g. operating table) • both castors with brake mounted at the short side of the base • solid manual level allows setting telescopic upper part at required height • a brake prevents exceeding the maximum height setting • upper section fit with smooth finished removable instrument tray Material: • high resistance to corrosion (tropical environment) • frame and tray: Austentic stainless steel, gards 304 • caster frame Intracket-steel or nylon • caster wheel: single wheel, mold on type, non-hooded (for easy maintenance), anti-static (for 4) • wheel bearing: seeled bearing in the swivel and the wheel • wheel bearing: seeled bearing in the swivel and the wheel • wheel single wheel; in the swivel and the wheel • wheel searing: seeled bearing in the swivel and the wheel • swivel is ball bearing Dimension: • Overall (81-90) x (50-55) x (90-100) cm (n'wft) • frame: 2.7-3.3 cm (outside, across), 1.5 mm thickness • thickness shelves: 1.35-1.5mm • swivel castor wheel: 3x10 cm (wfdiemeter) • carrying capacity: 100kg • long continued to the same and the structure of the same and the same			heavy carriage mounted on 4 swivel castors of which two with brake and 4 with anti-			
short side of the base - solid manual level allows setting telescopic upper part at required height - a brake prevents exceeding the maximum height setting - upper section fit with smooth finished removable instrument tray Material: - high resistance to corrosion (tropical environment) - frame and tray: Austentitic stainless steel, garde 304 - castor frame/ bracket:steel or ny/on - caster brake: total-look type (wheel and rotational look) - caster wheel: single wheel, mold on type, non-hooded (for easy maintenance), anti-static (for 4) - wheel bearing: sealed bearing in the swivel and the wheel - swivel is ball bearing - Overall (31-30) x (50-55) x (90-100) cm (/N*h) - trame: 2.7-3.3 cm (outside, across), 1.5 mm thickness - thickness shelves: 1.35-1.5mm - swivel castor wheel: 3x10 cm (w*diameter) - carrying capacity: 100kg - knockdown construction; yes 1 143,000.00 - forceps, solvroeder-braun uterine tenaoutum, 9.75 in (24.8 cm) - forceps, sopnge, foerster, straight,9.5in (24.1 cm) - sub-total			positioning under low clearance table (e.g			
upper part at required height a brake prevents exceeding the maximum height setting upper section fit with smooth finished removable instrument tray Materiat: inigh resistance to corrosion (tropical environment) inigh resistance to corrosion (tropical environment) inigh resistance to corrosion (tropical environment) inight resistanc			The state of the s			
a brake prevents exceeding the maximum helight setting buper section fit with smooth finished removable instrument tray high resistance to corrosion (tropical environment) frame and tray: Austentitic stainless steel, garde 304 castor framel bracket-steel or nylon caster brake: total-lock type (wheel and rotational lock) caster wheel: single wheel, mold on type, non-hooded (for easy maintenance), anti-static (for 4) wheel bearing: sealed bearing in the swivel and the wheel swivel is ball bearing Dimension: Overall (61-90) x (50-55) x (90-100) cm (("w"h)) frame: 2.7-3.3 cm (outside, across), 1.5 mm thickness thickness shelves: 1.35-1.5mm swivel castor wheel: 3x10 cm (w"diameter) carrying capacity: 100kg hoodedown construction: yes UDI INSERTION SET cup, lodine forceps, schroeder-braun uterine tenaculum, 9.75 in (24.8 cm) sousd, uterine, sims, 13 in (33.3cm) stern graduated in cm sub-total sub-total			CON ANAMARY IN CONTROL STATE OF THE STATE OF			
Material:						
high resistance to corrosion (tropical environment)			1.1			
environment) • frame and tray: Austentitic stainless steel, garde 304 • caster frame/ bracket:steel or nylon • caster brake: total-lock type (wheel and rotational lock) • caster wheel: single wheel, mold on type, non-hooded (for easy maintenance), anti-static (for 4) • wheel bearing: sealed bearing in the swivel and the wheel • swivel is ball bearing Dimension: • Overall (81-90) x (50-55) x (90-100) cm (l*w*h) • frame: 2.7-3.3 cm (outside, across), 1.5 mm thickness • thickness shelves: 1.35-1.5mm • swivel castor wheel: 3x10 cm (w*diameter) • carrying capacity: 100kg • knockdown construction: yes 10 ID INSERTION SET • forceps, schroeder-braun uterine tenaculum, 9.75 in (24.8 cm) • sound, uterine, sims, 13 in (33.3cm) stern graduated in cm • soissors, operating, amyo, curved, 6.75 in (17.1 cm) sub-total			Material:			
frame and tray: Austeritic stainless steel, garde 304		-				
castor frame/ bracket:steel or nylon caster brake: total-lock type (wheel and rotational lock) caster wheel: single wheel, mold on type, non-hooded (for easy maintenance), anti-static (for 4) wheel bearing: sealed bearing in the swivel and the wheel swivel is ball bearing Dimension: Overall (81-90) x (50-55) x (90-100) cm (("w"h)) frame: 2,7-3.3 cm (outside, across), 1.5 mm thickness thickness shelves: 1.35-1.5mm swivel castor wheel: 3x10 cm (w"diameter) carrying capacity: 100kg carrying capacity: 100kg carrying capacity: 100kg cup, iodine forceps, schroeder-braun uterine tenaculum, 9,75 in (24.8 cm) forceps, sponge, foerster, straight,9.5in (24.1 cm) sub-total sub-total sub-total 150,350.0			frame and tray: Austenitic stainless steel,			
caster brake: total-lock type (wheel and rotational lock) caster wheel: single wheel, mold on type, non-hooded (for easy maintenance), anti-static (for 4) wheel bearing: sealed bearing in the swivel and the wheel swivel is ball bearing Dimension: Overall (81-90) x (50-55) x (90-100) cm (1*w*h)						
caster wheel: single wheel, mold on type, non-hooded (for easy maintenance), anti-static (for 4) wheel bearing: sealed bearing in the swivel and the wheel swivel is ball bearing Dimension: Overall (81-90) x (50-55) x (90-100) cm (1'w*h) frame: 2.7-3.3 cm (outside, across), 1.5 mm thickness thickness shelves: 1.35-1.5mm swivel castor wheel: 3x10 cm (w*diameter) carrying capacity: 100kg knockdown construction: yes 2024-0154-4411 set IUD INSERTION SET 1 143,000.00 forceps, schroeder-braun uterine tenadum, 9.75 in (24.8 cm) forceps, sponge, foerster, straight,9.5in (24.1 cm) sound, uterine, sims, 13 in (33.3cm) sterm graduated in cm scissors, operating, amyo, curved, 6.75 in (17.1 cm) sub-total 150,350.0			caster brake: total-lock type (wheel and			33436-333
and the wheel			caster wheel: single wheel, mold on type, non-hooded (for easy maintenance), anti-static			
Swivel is ball bearing Dimension: Overall (81-90) x (50-55) x (90-100) cm (*w*h)			2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2			
Dimension: Overall (81-90) x (50-55) x (90-100) cm (1*w*h) frame: 2.7-3.3 cm (outside, across), 1.5 mm thickness thickness shelves: 1.35-1.5mm swivel castor wheel: 3x10 cm (w*diameter) carrying capacity: 100kg knockdown construction: yes 2024-0154-4411 set IUD INSERTION SET 1 143,000.00 143,000.0 cup, iodine forceps, schroeder-braun uterine tenaculum, 9.75 in (24.8 cm) forceps, sponge, foerster, straight, 9.5in (24.1 cm) sound, uterine, sims, 13 in (33.3cm) stern graduated in cm scissors, operating, amyo, curved, 6.75 in (17.1 cm) sub-total 150,350.0						
(I*w*h) • frame: 2.7-3.3 cm (outside, across), 1.5 mm thickness • thickness shelves: 1.35-1.5mm • swivel castor wheel: 3x10 cm (w*diameter) • carrying capacity: 100kg • knockdown construction: yes 2024-0154-4411 set IUD INSERTION SET 1 143,000.00 143,000.0 • cup, iodine • forceps, schroeder-braun uterine tenaculum, 9.75 in (24.8 cm) • forceps, sponge, foerster, straight, 9.5in (24.1 cm) • sound, uterine, sims, 13 in (33.3cm) stern graduated in cm • scissors, operating, amyo, curved, 6.75 in (17.1 cm) sub-total 150,350.0						
frame: 2.7-3.3 cm (outside, across), 1.5 mm thickness						
swivel castor wheel: 3x10 cm (w*diameter) carrying capacity: 100kg knockdown construction: yes 2024-0154-4411 set IUD INSERTION SET			 frame: 2.7-3.3 cm (outside, across), 1.5 			
• carrying capacity: 100kg • knockdown construction: yes 2024-0154-4411 set IUD INSERTION SET 1 143,000.00 143,000.0 • cup, iodine • forceps, schroeder-braun uterine tenaculum, 9.75 in (24.8 cm) • forceps, sponge, foerster, straight, 9.5 in (24.1 cm) • sound, uterine, sims, 13 in (33.3 cm) stern graduated in cm • scissors, operating, amyo, curved, 6.75 in (17.1 cm) sub-total 150,350.0			thickness shelves: 1.35-1.5mm			
Nockdown construction: yes 2024-0154-4411 set IUD INSERTION SET 1 143,000.00 143,000.00			swivel castor wheel: 3x10 cm (w*diameter)			
2024-0154-4411 set IUD INSERTION SET 1 143,000.00 143,000.00 • cup, iodine • forceps, schroeder-braun uterine tenaculum, 9.75 in (24.8 cm) • forceps, sponge, foerster, straight,9.5in (24.1 cm) • forceps, sponge, foerster, straight,9.5in (24.1 cm) • sound, uterine, sims, 13 in (33.3cm) stern graduated in cm • scissors, operating, amyo, curved, 6.75 in (17.1 cm) • scissors, operating, amyo, curved, 6.75 in (17.1 cm) • 150,350.0			carrying capacity: 100kg			
cup, iodine forceps, schroeder-braun uterine tenaculum, 9.75 in (24.8 cm) forceps, sponge, foerster, straight,9.5in (24.1 cm) sound, uterine, sims, 13 in (33.3cm) stern graduated in cm scissors, operating, amyo, curved, 6.75 in (17.1 cm) sub-total 150,350.0			knockdown construction: yes			
forceps, schroeder-braun uterine tenaculum, 9.75 in (24.8 cm) forceps, sponge, foerster, straight,9.5in (24.1 cm) sound, uterine, sims, 13 in (33.3cm) stern graduated in cm scissors, operating, amyo, curved, 6.75 in (17.1 cm) sub-total 150,350.0	2024-0154-4411	set		1	143,000.00	143,000.00
tenaculum, 9.75 in (24.8 cm) • forceps, sponge, foerster, straight, 9.5 in (24.1 cm) • sound, uterine, sims, 13 in (33.3 cm) stern graduated in cm • scissors, operating, amyo, curved, 6.75 in (17.1 cm) sub-total 150,350.0						
(24.1 cm) sound, uterine, sims, 13 in (33.3cm) stern graduated in cm scissors, operating, amyo, curved, 6.75 in (17.1 cm) sub-total 150,350.0			tenaculum, 9.75 in (24.8 cm)			
graduated in cm ■ scissors, operating, amyo, curved, 6.75 in (17.1 cm) sub-total 150,350.0			(24.1 cm)			
(17.1 cm) sub-total 150,350.0						
			10 A 180 (A)			
						150,350.00
		No.	-page 2 of 5-			

Stock/Property No.	Unit	Description	Quantity	Unit Cost	Amount
		speculum, vaginal, graves, medium (1.38 in (3.5cm) x 4 in (10.2 cm)			
		speculum vaginal, graves large (4.75inch x 1.5 inch)			
2024-0155-4411	unit	NEBULIZER	1	15,000.00	15,000.00
		VMED Pulmo Aide Nebulizer Heavy Duty Devilbiss 5650			
2024-0156-4411	unit	OXYGEN TANK WITH REGULATOR	1	31,250.00	31,250.00
		5L oxygen concentrator 24/7 heavy duty			La distribution of the comment of
		medical and in- house use, oxygen purity of 93% +/-3% at 5LPM			
		multiple users function		1 700 00	
2024-0157-4411	unit	REVOLVING STOOL	1	1,700.00	1,700.00
	saionai iomiyoskodi	All stainless steel shall be 300 grades series			
		Padded Seat			
		Standard Adjustable height			
		with foot rest			
		five stroke base and wheels			
2024-0158-4411	unit	DELIVERY SET	1	36,400.00	36,400.00
		OB-gyne instrument stainless, reusable			
		Sterilizable			*****
-		high tensile			
2024-05-110-0004- 4411	unit	autoclavable, complete set DELIVERY TABLE WITH DETACHABLE STIRRUPS WITH MATTRESS WITH FOOTSTOOL	1	124,860.00	124,860.00
4411		TABLE			0.0000000000000000000000000000000000000
		Length: 1600mm-1900mm			
		Width : 600mm-900mm			
		Height: adjustable at least 550-900mm			-
	***************************************	Load capacity: maximum of 200kg			
		Auxiliary table (leg part) removable/ adjustable			
	-	Adjustable backrest: 600-900mm x 400- 600mm (range)			
		Fold upward: at least 60 degree			
		Fold downward: at least 5 degree			
		stainless steel frame & table top (stainless steel shall be 300 grade series)			
		Trendelenburg /Reverse trendelenburg function of up to 10 degrees			
		manual, hydraulic mechanism			
		MATTRESS • detachable			The second second second second
		high density sponge & high quality leather		<u> </u>	· · · · · · · · · · · · · · · · · · ·
		at least 2 inches thickness			
		ARM REST			
		• 2pcs			
		detachable and/or adjustable			
		with detachable arm sling/ strains			
		ACCESSORIES			
		2 padded stirrups (knee crutches)		-	
		detachable and/or adjustable swing out at least 45 degree			
		hand grips (waist grab handle)			
		 1 stainless steel footstool single step (stainless steel shall be 300 grade series) 			
		sub-total sub-total		·	209,210.00

Stock No.	Unit	Description	Quantity	Unit Cost	Amount
		 1 stainless steel kick bucket of filth (2-3 gallons)(stainless steel shall be 300 grade series) 			
		Anesthesia screen (detachable)			
		Stainless steel IV pole with 2 hooks (stainless steel 300 grade series)			
		revolving adjustable chair without backrest			-101
2024-0159-4411	unit	DRESSING CART	1	23,600.00	23,600.00
		dressing trolley, with two flat non- removable shelves	-		
		heavy carriage mounted on 4 swivel castors, of which two with brake			
		 transfer bars connect all lower distal portions of the 4 base, providing maximal structural strength 			
		 Shelves have smooth finishing allowing for easy cleaning 			
		 push bar handle fit on one short side 			
		 both castors with brake are mounted at the push bar handle side 			
		top and bottom shelves have guard rails, along one length and both widths			
		with protective bumpers at all four corners			
		Material:			
		High resistance to corrosion (tropical environment)	V U CO 42 5 X X H O O H CO 900 - 5		
	2	Frame and shelves: Austenitic stainless steel grade 304			
		Castor frame/ bracket: steel or nylon			
		Caster brake: total -lock type (wheel and rotational lock)			
72		 Caster wheel: single wheel, mold on type, non-hooded (for easy maintenance) 			
		Wheel bearing: sealed bearing in the swivel and the wheel			
		swivel is ball-bearing			
2024-0160-4411	unit	EMERGENCY LIGHT	2	1,316.00	2,632.00
		emergency, portable lamps, twinhead LED emergency light			
2024-0161-4411	unit	BP APPARATUS STAND TYPE, ADULT AND PEDIA	1	7,000.00	7,000.00
		 stand type; adult and pedia 			
		complete set sphygmomanometer and stethoscope, high quality			
2024-0162-4411	unit	OXYGEN CARRIER	1	8,000.00	8,000.00
		oxygen tank trolley, 50lbs capacity, high quality			
2024-0163-4411	unit	CHOLESTEROL METER with needle and 100 strips, with expiration of at least 3 years	1	15,300.00	15,300.00
2024-0164-4411	unit	DIGITAL THERMOMETER	1	291.00	291.00
		both for baby and adult			CONTRACTOR AND ADDRESS OF THE PARTY OF THE P
		infrared, multi- function electronic			
	Vords):	FOUR HUNDRED SEVENTY EIGHT THOUSAND NINE HUN			

In case of failure to make the full delivery within the time specified above, a penalty of one-tenth (1/10) of one percent for every day of delay shall be imposed on the undelivered item/s.				
Conforme: Jenny COM up*	Very truly yours,			
PARACLETE DIAGNOSTIC ENTERPRISES OPC Signature over defined Name of Supplier STAND CONTINUE Date WARM DE WOR	ELSIE D. VISCA Signature over Printed Name of Authorized Official Municipal Mayor Designation			
(In case of Negotiated Purchase pursuant to Section 369 (a) of RA 7160, this portion must be accomplished.)				
Approved per Sanggunian Resolution No.:				
Certified Correct:				
N/A Secretary to the Sanggunian	Date			